



# GHS SAFETY DATA SHEET

Date Revised: APR 2018  
Supersedes: APR 2015

## WELD-ON® 845™ Low VOC 2-Component Adhesive

### SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** WELD-ON® 845™ Low VOC 2-Component Adhesive  
**PRODUCT USE:** 2-Component Cartridge, Low VOC Adhesive for bonding large diameter PVC and CPVC pipe and fittings; also bonds ABS, Styrene, Acrylic, FRP, (fiberglass-reinforced polyester), aluminum (non-anodized), other metals, concrete, clay and other materials to themselves or to dissimilar materials  
**SUPPLIER:** **MANUFACTURER:** IPS Corporation  
 600 Ellis Road, Durham, NC 27703 - USA  
 P.O. Box 12729, Research Triangle Park, NC 27709 - USA  
 Tel. 1-919-598-2400  
**EMERGENCY:** Transportation: CHEMTEL Tel. 800.255-3924, +1 813-248-0585 (International) **Medical:** CHEMTEL Tel. 800.255-3924, +1 813-248-0585 (International)

### SECTION 2 - HAZARDS IDENTIFICATION

#### GHS CLASSIFICATION:

<u>Health</u>		<u>Environmental</u>		<u>Physical</u>	
Acute Toxicity:	Category 4	Acute Toxicity:	Category 3	Flammable Liquid:	Category 2
Skin Irritation:	Category 2	Chronic Toxicity:	Category 4		
Skin Sensitization:	Category 1				
Eye:	Category 2				

#### GHS LABEL:



**Signal Word:**  
Danger

**WHMIS CLASSIFICATION:** CLASS B, DIVISION 2  
CONTROLLED PRODUCT CLASS D, DIVISION 2B

<u>Hazard Statements</u>		<u>Precautionary Statements</u>	
H-225 Highly flammable liquid and vapor	H-317 May cause irritation/allergic skin reaction	P-260 Do not breathe vapor	P-233 Keep container closed P-271 Use in well-ventilated area

### SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS#	EINECS #	REACH Pre-registration Number	CONCENTRATION
				% by Weight
<b>Component "A" (Base Resin)</b>				
Methyl Methacrylate Monomer (MMA),* Stabilized	80-62-6	201-297-1	05-2116297731-37-0000	45 - 65
Bis (2,4-dicumylphenyl) neopental diphosphite	154862-43-8	421-920-2	N/A	1 - 3%
N,N-Dimethyl-p-toluidine #	99-97-8	202-805-4	N/A	0.0 - 1
<b>Component "B" (Catalyst-Initiator)</b>				
Benzoyl Peroxide (BPO)*	94-36-0	202-327-6	05-2116297715-31-0000	1 - 10

All of the constituents of this adhesive product are listed on the TSCA inventory of chemical substances maintained by the US EPA, or are exempt from that listing.  
 \*Indicates this chemical is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 (40CFR372).  
 # indicates that this chemical is found on Proposition 65's List of chemicals known to the State of California to cause cancer or reproductive toxicity.

### SECTION 4 - FIRST AID MEASURES

**Contact with eyes:** Flush eyes immediately with plenty of water for 15 minutes and seek medical advice immediately.  
**Skin contact:** Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water. If irritation develops, seek medical advice.  
**Inhalation:** Remove to fresh air. If breathing is stopped, give artificial respiration. If breathing is difficult, give oxygen. Seek medical advice.  
**Ingestion:** Rinse mouth with water. Give 1 or 2 glasses of water or milk to dilute. Do not induce vomiting. Seek medical advice immediately.  
**Likely Routes of Exposure:** Inhalation, Eye and Skin Contact  
**Acute symptoms and effects:**  
**Inhalation:** Severe overexposure may result in nausea, dizziness, headache. Can cause drowsiness, irritation of eyes and nasal passages.  
**Eye Contact:** Vapors slightly uncomfortable. Overexposure may result in severe eye injury with corneal or conjunctival inflammation on contact with the liquid.  
**Skin Contact:** Liquid contact may remove natural skin oils resulting in skin irritation. Dermatitis may occur with prolonged contact.  
**Ingestion:** May cause nausea, vomiting, diarrhea and mental sluggishness.  
**Chronic (long-term) effects:** None known to humans

### SECTION 5 - FIREFIGHTING MEASURES

**Suitable Extinguishing Media:** Dry chemical powder, carbon dioxide gas, foam, Halon, water fog.  
**Unsuitable Extinguishing Media:** Water spray or stream.  
**Exposure Hazards:** Inhalation and dermal contact  
**Combustion Products:** Oxides of carbon, oxides of nitrogen, hydrocarbons, acrid smoke and toxic gases and phosphorus compounds.  
**Protection for Firefighters:** Self-contained breathing apparatus or full-face positive pressure air-supply masks.

	Health	Flammability	Reactivity	PPE	HMIS	NFPA	0-Minimal
	2	3	2	B	2	3	1-Slight 2-Moderate 3-Serious 4-Severe

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Keep away from heat, sparks and open flame.  
 Provide sufficient ventilation, use explosion-proof exhaust ventilation equipment or wear suitable respiratory protective equipment.  
 Prevent contact with skin or eyes (see section 8).  
**Environmental Precautions:** Prevent product or liquids contaminated with product from entering sewers, drains, soil or open water course.  
**Methods for Cleaning up:** Contain spill with sand or other inert adsorbent or absorbent material. Use non-sparking tools.  
 Transfer to a closable vessel (Metal or polyethylene [PE])

### SECTION 7 - HANDLING AND STORAGE

**Handling:** Avoid breathing of vapor, avoid contact with eyes, skin and clothing.  
 Keep away from ignition sources, use only electrically grounded handling equipment and ensure adequate ventilation/fume exhaust hoods.  
 Do not eat, drink or smoke while handling.  
**Storage:** Store between 50° - 80°F (10° - 27°C). Keep container tightly closed when not in use.  
 Keep away from ignition sources and incompatible materials. Follow all precautionary information on container label and product bulletins.

### SECTION 8 - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:	Component	ACGIH TLV	ACGIH STEL	OSHA PEL	OSHA STEL	OSHA PEL-Ceiling	CAL/OSHA PEL	CAL/OSHA Ceiling	CAL/OSHA STEL
		Methyl Methacrylate Monomer	50 ppm	100 ppm	100 ppm	N/E	N/E	50 ppm	N/E
Bis (2,4-dicumylphenyl) neopental diphosphite (dust)	N/E	N/E	N/E	N/E	N/E	15 mg/m3	N/E	N/E	N/E
N,N-Dimethyl-p-toluidine	N/E	N/E	N/E	N/E	N/E	N/E	N/E	N/E	N/E
Benzoyl Peroxide	5 mg/m <sup>3</sup>	N/E	N/E	5 mg/m <sup>3</sup>	N/E	N/E	N/E	N/E	N/E

#### Hazards Not Otherwise Classified (HNOC)

**N,N-Dimethyl-p-toluidine** Chemical known in the state of California to cause cancer.

**Engineering Controls:** Use local exhaust as needed.

**Monitoring:** Maintain breathing zone airborne concentrations below exposure limits.

#### Personal Protective Equipment (PPE):

**Eye Protection:** Avoid contact with eyes, wear splashproof chemical goggles, face shield, safety glasses (spectacles) with brow guards and side shields,

**Skin Protection:** Prevent contact with the skin as much as possible. Butyl rubber gloves should be used for frequent immersion.

Use of solvent-resistant gloves or solvent-resistant barrier cream should provide adequate protection when normal adhesive application practices and procedures are used for making structural bonds.

**Respiratory Protection:** Use in a well-ventilated room. Use local exhaust ventilation to remove airborne contaminants from employee breathing zone and to keep contaminants below levels listed above. With normal use, the Exposure Limit Value will not usually be reached. When limits approached, use respiratory protection equipment.

### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b> "A" Tan, heavy viscous liquid; "B" Clear low viscosity liquid <b>Odor:</b> "A" Acrid Odor, "B" Mild <b>P.H.:</b> Not Applicable <b>Boiling Point:</b> "A" 100.5°C (212.9°F) Based on first boiling component: MMA " B" Decomposes <b>Flash Point:</b> "A" 11.5°C (52.7°F) T.C.C. based on MMA, "B" 84°C (184°F) for BPO <b>Specific Gravity:</b> "A" 1.06 @23°C (73°F), "B" 1.295 @23°C (73°F) <b>Solubility:</b> "A" Slight in Water (MMA), "B" Insoluble in Water <b>Auto-ignition Temperature:</b> "A" 421°C (789.8°F); MMA, "B": Not Established <b>Decomposition Temperature:</b> "A" Not Applicable, "B" - 110°C (230°F) <b>VOC Content:</b> "A" ≤ 50 g/l mixed, "B" - None	<b>Odor Threshold:</b> "A" 0.75 ppm; MMA, "B" Slight <b>Active Oxygen Content:</b> <1 % <b>Evaporation Rate:</b> "A" - > 1.0, "B" - <1 (BUAC = 1) <b>Flammability:</b> "A" Category 2, "B" Category 4 <b>Flammability Limits:</b> LEL: "A" 1.6% based on MMA UEL: "A" 12.5% based on MMA <b>LEL &amp; UEL:</b> "B" - Not Established <b>Vapour Pressure:</b> "A" 29 mm Hg @ 20°C (68°F); MMA <b>Vapour Density:</b> "A" >3 (Air = 1), "B" - N/E
--	---

### SECTION 10 - STABILITY AND REACTIVITY

<b>Stability:</b> Stable, unless heated <b>Hazardous decomposition products:</b> None in normal use. Oxides of carbon, oxides of nitrogen, hydrocarbons, acrid smoke and toxic gases and phosphorus compounds. <b>Conditions to avoid:</b> Keep away from direct sunlight, heat, sparks, open flame and other ignition sources. <b>Incompatible Materials:</b> Reducing and oxidizing agents and metal contaminants	
--	--

### SECTION 11 - TOXICOLOGICAL INFORMATION

<b>Toxicity:</b> Methyl Methacrylate Monomer (MMA) Benzoyl Peroxide Bis (2,4-dicumylphenyl) neopental diphosphite	<b>LD50</b> Oral: 7900 mg/kg (rat), Dermal: >35000 mg/kg (rabbit) Oral: 6400 mg/kg (rat) Oral: 5000 mg/kg (rat), Dermal: >2000 mg/kg (rat)	<b>LC50</b> Inhalation: 3 hrs. 7093 PPM (rat) Oral: 2 mg/l 96 hours (guppy) Not Established	<b>Target Organs</b> STOT SE3 Not Established Not Established
--	---	--	--

Reproductive Effects	Teratogenicity	Mutagenicity	Embryotoxicity	Sensitization to Product	Synergistic Products
Not Established	Not Established	Not Established	Not Established	Not Established	Not Established

### SECTION 12 - ECOLOGICAL INFORMATION

<b>Ecotoxicity:</b> None known <b>Mobility:</b> In normal use, emission of volatile organic compounds (VOC's) to the air takes place, typically at a rate of ≤50 g/l <b>Degradability:</b> Not Established <b>Bioaccumulation:</b> Not Established	
---	--

### SECTION 13 - WASTE DISPOSAL CONSIDERATIONS

Follow local and national regulations. Consult local disposal expert.

### SECTION 14 - TRANSPORT INFORMATION

<b>Proper Shipping Name:</b> Adhesives <b>Hazard Class:</b> 3 <b>Secondary Risk:</b> None <b>Identification Number:</b> UN 1133 <b>Packing Group:</b> PG II <b>Label Required:</b> Class 3 Flammable Liquid <b>Marine Pollutant:</b> NO	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">EXCEPTION for Ground Shipping</th> </tr> </thead> <tbody> <tr> <td>DOT Limited Quantity: Up to 5L per inner packaging, 30 kg gross weight per package.</td> </tr> <tr> <td>Consumer Commodity: Depending on packaging, these quantities may qualify under DOT as "ORM-D" .</td> </tr> </tbody> </table> <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th colspan="2" style="text-align: center;">TDG INFORMATION</th> </tr> </thead> <tbody> <tr> <td>TDG CLASS:</td> <td>FLAMMABLE LIQUID 3</td> </tr> <tr> <td>SHIPPING NAME:</td> <td>ADHESIVES</td> </tr> <tr> <td>UN NUMBER/PACKING GROUP:</td> <td>UN 1133, PG II</td> </tr> </tbody> </table>	EXCEPTION for Ground Shipping	DOT Limited Quantity: Up to 5L per inner packaging, 30 kg gross weight per package.	Consumer Commodity: Depending on packaging, these quantities may qualify under DOT as "ORM-D" .	TDG INFORMATION		TDG CLASS:	FLAMMABLE LIQUID 3	SHIPPING NAME:	ADHESIVES	UN NUMBER/PACKING GROUP:	UN 1133, PG II
EXCEPTION for Ground Shipping												
DOT Limited Quantity: Up to 5L per inner packaging, 30 kg gross weight per package.												
Consumer Commodity: Depending on packaging, these quantities may qualify under DOT as "ORM-D" .												
TDG INFORMATION												
TDG CLASS:	FLAMMABLE LIQUID 3											
SHIPPING NAME:	ADHESIVES											
UN NUMBER/PACKING GROUP:	UN 1133, PG II											

### SECTION 15 - REGULATORY INFORMATION

<b>Precautionary Label Information:</b> Highly Flammable, Irritant <b>Symbols:</b> F, Xi <b>Risk Phrases:</b> R-11 Highly Flammable R-36/37/38 Irritating to eyes, respiratory system and skin	<b>Ingredient Listings:</b> USA TSCA, Europe EINECS, Canada DSL, Australia AICS, Korea ECL/TCCL, Japan MITI (ENCS) R-43 May cause sensitization by skin contact. R-53 May cause long-term adverse effects in the aquatic environment.
<b>Safety Phrases:</b> S-2 Keep out of reach of children S-3 Keep in a cool place S-7 Keep container tightly closed S-24/25 Avoid contact with skin and eyes.	S-26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice S-36/37/39 Wear suitable protective clothing, gloves and eye/face protection S-46 If swallowed, seek medical advice immediately and show this container or label S-61 May cause harm to the unborn child

### SECTION 16 - OTHER INFORMATION

<b>Specification Information:</b> <b>Department issuing data sheet:</b> <b>E-mail address:</b> <b>Training necessary:</b> <b>Reissue date / reason for reissue:</b> <b>Intended Use of Product:</b>	IPS, Safety Health & Environmental Affairs <EHSinfo@ipscorp.com> Yes, training in practices and procedures contained in product literature. 4/6/2018 / Updated GHS Standard Format Reactive acrylic adhesive bonding/cementing plastics and other substrates	All ingredients are compliant with the requirements of the European Directive on RoHS (Restriction of Hazardous Substances). Not recommended for use on PTFE, Silicone, Polypropylene, Polyethylene and other Polyolefin's or joints with an interference fit.
--	--	---

This product is intended for use by skilled individuals at their own risk. The information contained herein is based on data considered accurate based on current state of knowledge and experience. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.